






Common Mode Choke

UU9.8 Series


UU9.8 Type 1



Dimensions:(mm)




SCHEMATIC:





• WINDING.STRA


UU9.8 Type 2



Dimensions:(mm)



SCHEMATIC:



• WINDING.STRA

APPLICATIONS:

- Off-line power supplies.
- Protects AC input from effects of switching regulators
- DC - DC Converters
- Computer , TV , VCR , audio and office equipment

ELECTRICAL CHARACTERISTICS:

Patr Number	Inductance (mH)Min	DCR Max.(Ohms)	Irms(A)
PZ-UU9.8-0.39	0.39	0.08	1.6
PZ-UU9.8-0.68	0.68	0.13	1.2
PZ-UU9.8-0.90	0.9	0.19	1
PZ-UU9.8-1.4	1.4	0.3	0.8
PZ-UU9.8-2.1	2.1	0.48	0.65
PZ-UU9.8-3.3	3.3	0.74	0.5
PZ-UU9.8-4.9	4.9	1.2	0.4
PZ-UU9.8-.74	7.4	1.8	0.35
PZ-UU9.8-11.5	11.5	2.8	0.27
PZ-UU9.8-18.7	18.7	4.45	0.22

★Design to customer requirement

- 1.Test Frequency : 1KHZ/0.25V
- 2.Operating Temperature Range : -50℃ to + 130 ℃ range is application specific
- 3.Winding Temperature Rise (at Rated Current) : 60K Max
- 4.Packaging : Supplied in bulk packaging.